

## REF119 MIYOSHI SHIP BUILDING CO., JAPAN BUILT: 1980-10-29



### Broker Info

Name: IBRAHIM YIN  
First Name: IBRAHIM  
Website: <http://www.vanocean.com/cn/>  
Phone: +010 (516) XXX-XX  
Address: Room 2213 The Spaces  
International Center,  
No.8 Dong Da Qiao  
Road, Chaoyang  
District, Beijing, Chi

### Listing details

Title: REF119 MIYOSHI SHIP BUILDING CO., JAPAN  
BUILT: 1980-10-29  
Ref No: RF159107  
Price: 2,000,000.00  
Built: 1980  
LDT: 4,274  
Flag: KIRIBATI  
Model: REEFER CARRIER  
Condition:

### Additional information

Description:  
NO. REF119  
TYPE REEFER CARRIER  
PORT OF REGISTRY TARAWA  
FLAG KIRIBATI  
BUILT built\_in KEEL LAID: 1980-06-14;  
BUILT: 1980-10-29  
BUILT PLACE MIYOSHI SHIP BUILDING CO., JAPAN  
CLASS ISCLASS (INTERNATIONAL SHIP CLASSIFICATION)  
SS  
DD  
LOA 112.90 M

LBP 105.00 M  
BEAM 16.00 M  
DEPTH 9.72 M  
DRAFT SUMMER: 6.516 M;  
WINTER: 6.381 M;  
TROPICAL: 6.651 M;  
FRESH: 6.645 M;  
TROPICAL FRESH: 6.780 M;  
MAXIMUM SUMMER DRAFT: 6.78 M  
DISPLACEMENT AT SUMMER DRAFT 6994.80 MT  
PANAMA GT/NT 4586.78 / 3240.22  
SUEZ GT/NT 4295.18 / 3239.75  
GT 4056 MT  
NT 1678 MT  
DWT SUMMER: 4274 MT  
LIGHTWEIGHT 2719.81 MT  
FLOOR SPACE CAPACITY  
GEAR DERRICKS 6x3 MT  
ME KOBE MITSUBISHI  
TYPE 6UEC52 / 105D  
SUPERCHARGED, TWO STROKE CYCLE, SINGLE ACTING CROSS HEAD, DIRECT  
REVERSING DIESEL ENGINE  
MAX CONTINUOUS OUTPUT: 6200BHP AT 175RPM  
CONTINUOUS SERVICE OUTPUT: 5580 BHP AT 169RPM  
AE/GENERATOR 3xDAIHATSU TYPE DS 18A  
KW/RPM: 400/900  
VOLT/HZ: 440/60  
SPEED/CONSUMPTION 17 KTS  
ME FUEL OIL CONS SEA SPEED LADEN 15MT / BALLAST 13MT / ECO SPEED LADEN 13MT /  
ECO SPEED BALLAST 11MT  
ME SYSTEM LUB OIL CONS 50LT  
ME CYLINDER OIL CONS 160LT  
DIESEL GENERATOR BLENDED OIL CONS LADEN 3.5MT / BALLAST 1.8MT / PORT IDLE  
1.5MT / PORT WORKING 2.5MT / LUB OIL CONS 40LT  
BOILER PORT CONS 0.6MT  
FUEL TYPE  
HOLD NUMBER 3  
HATCH NUMBER 3  
HATCH SIZE NO.1: 6.50x5.50 M  
NO.2 & 3: 6.60x5.50M  
COMPARTMENT 9  
DECKS  
DECK AREA 2068.31 SQM  
DECK HEIGHT  
CAPACITY (CBFT) 178367

CAPACITY (CBM) 5050.71  
TYPE OF THE VENT SYSTEM  
VENT  
TEMPERATURE -30/+15 DC  
P&I CLUB MARITIME MUTUAL INSURANCE ASSOCIATION (NZ) LTD  
TPC AT SUMMER DRAFT 13.42  
PROPELLER NAKASHIMA PROPELLER CO., LTD  
5 BLADES SOLID TYPE, DIAM=370MM, PITCH=3525MM  
WATER BALLAST CAPACITY 89 MT (FORE PEAK ONLY)  
FRESH WATER CAPACITY 125 MT  
FUEL OIL CAPACITY 900 MT  
DIESEL OIL CAPACITY 180 MT  
LUB OIL TANK 81.54 CBM  
HATCH TYPE MACGREGOR HATCHCOVERS HYDRAULICALLY OPERATED  
MACGREGOR TWEENDECK COVERS FOLDING TYPE, WIRE OPERATION  
COOLING SYSTEM DIR EXPANSION R-22  
AIR CHANGES 90 / HOUR FULL – 40 / HOUR SLOW  
AIR RENEWALS 4 / HOUR  
COOLING SECTIONS 6  
1A / 1BC / 2A / 2BC / 3A / 3BC  
GRATINGS HOLED WOODEN – MAX STRENGTH FOR FORKLIFTS (4 PNEUMATIC TIRES)  
5MT  
DISTANCE FROM BOW TO NO.1 HATCH CENTER: 33.4 M  
NO.2 HATCH CENTER: 53.6 M  
NO.3 HATCH CENTER: 74.6 M  
BRIDGE: 83.3 M  
DELIVERY PLACE AS WHERE SHE IS  
INSPECTION PLACE  
PRICE USD 2.0 MILLION

Posted:

12 years ago

