

REF119



Broker Info

Name: IBRAHIM YIN
First Name: IBRAHIM
Website: <http://www.vanocean.com/cn/>
Phone: +010 (516) XXX-XX
Address: Room 2213 The Spaces International Center, No.8 Dong Da Qiao Road, Chaoyang District, Beijing, Chi

Listing details

Title: REF119
Ref No: RF976180
Price: 1,600,000.00
Built: 1980
DWT: 4,274.99
LDT: 2,719.81
Flag: KIRIBATI
Model: Reefer
Condition:

Additional information

Description:
NO. REF119
TYPE REEFER
PORT OF REGISTRY TARAWA
FLAG KIRIBATI
BUILT built_in KEEL LAID: 1980-06-14;
BUILT: 1980-10-29
BUILT PLACE MIYOSHI SHIP BUILDING CO., JAPAN
CLASS ISCLASS (INTERNATIONAL SHIP CLASSIFICATION)
SS
DD
LOA 112.90 M

LBP 105.00 M
BEAM 16.00 M
DEPTH 9.72 M
DRAFT SUMMER: 6.516 M;
WINTER: 6.381 M;
TROPICAL: 6.651 M;
FRESH: 6.645 M;
TROPICAL FRESH: 6.780 M;
MAXIMUM SUMMER DRAFT: 6.78 M
DISPLACEMENT AT SUMMER DRAFT 6994.80 MT
PANAMA GT/NT 4586.78 / 3240.22
SUEZ GT/NT 4295.18 / 3239.75
GT 4056 MT
NT 1678 MT
DWT SUMMER: 4274.99 MT
LIGHTWEIGHT 2719.81 MT
FLOOR SPACE CAPACITY
GEAR DERRICKS 6x3 MT
ME KOBE MITSUBISHI
TYPE 6UEC52 / 105D
SUPERCHARGED, TWO STROKE CYCLE, SINGLE ACTING CROSS HEAD, DIRECT
REVERSING DIESEL ENGINE
MAX CONTINUOUS OUTPUT: 6200BHP AT 175RPM
CONTINUOUS SERVICE OUTPUT: 5580 BHP AT 169RPM
AE/GENERATOR 3xDAIHATSU TYPE DS 18A
KW/RPM: 400/900
VOLT/HZ: 440/60
SPEED/CONSUMPTION 17 KTS
ME FUEL OIL CONS SEA SPEED LADEN 15MT / BALLAST 13MT / ECO SPEED LADEN 13MT /
ECO SPEED BALLAST 11MT
ME SYSTEM LUB OIL CONS 50LT
ME CYLINDER OIL CONS 160LT
DIESEL GENERATOR BLENDED OIL CONS LADEN 3.5MT / BALLAST 1.8MT / PORT IDLE
1.5MT / PORT WORKING 2.5MT / LUB OIL CONS 40LT
BOILER PORT CONS 0.6MT
FUEL TYPE
HOLD NUMBER 3
HATCH NUMBER 3
HATCH SIZE NO.1: 6.50x5.50 M
NO.2 & 3: 6.60x5.50M
COMPARTMENT 9
DECKS
DECK AREA 2068.31 SQM
DECK HEIGHT
CAPACITY (CBFT) 178367

CAPACITY (CBM) 5050.71
TYPE OF THE VENT SYSTEM
VENT
TEMPERATURE -30/+15 DC
P&I CLUB MARITIME MUTUAL INSURANCE ASSOCIATION (NZ) LTD
TPC AT SUMMER DRAFT 13.42
PROPELLER NAKASHIMA PROPELLER CO., LTD
5 BLADES SOLID TYPE, DIAM=370MM, PITCH=3525MM
WATER BALLAST CAPACITY 89 MT (FORE PEAK ONLY)
FRESH WATER CAPACITY 125 MT
FUEL OIL CAPACITY 900 MT
DIESEL OIL CAPACITY 180 MT
LUB OIL TANK 81.54 CBM
HATCH TYPE MACGREGOR HATCHCOVERS HYDRAULICALLY OPERATED
MACGREGOR TWEENDECK COVERS FOLDING TYPE, WIRE OPERATION
COOLING SYSTEM DIR EXPANSION R-22
AIR CHANGES 90 / HOUR FULL – 40 / HOUR SLOW
AIR RENEWALS 4 / HOUR
COOLING SECTIONS 6
1A / 1BC / 2A / 2BC / 3A / 3BC
GRATINGS HOLED WOODEN – MAX STRENGTH FOR FORKLIFTS (4 PNEUMATIC TIRES)
5MT
DISTANCE FROM BOW TO NO.1 HATCH CENTER: 33.4 M
NO.2 HATCH CENTER: 53.6 M
NO.3 HATCH CENTER: 74.6 M
BRIDGE: 83.3 M
DELIVERY PLACE CHINA
INSPECTION PLACE CHINA
PRICE USD 1.6 MILLION
Posted: 12 years ago

